

Mortar

[Http://www.jeilchemical.com](http://www.jeilchemical.com)

JP-105

c. Curing time : 24 hours (temperature 25°C±5°C, humidity 60%)

1. Product use

- 1) High strength epoxy mortar flooring resin
- 2) Used for flooring required dustproof and abrasion resistance
- 3) Used for flooring required chemical resistance

2.Features

- 1) Superior adhesive property.
- 2) Superior mechanical strength including abrasion resistance, bending, compressive, impact strength, etc.
- 3) Superior chemical properties including chemical resistance, waterproofing, and solvent resistance.
- 4) Outstanding Non-slip property mixing with silica sand.

3. Others

- 1) Storage requirements
 - a. Store in room temperature (25°C±5°C)
 - b. Storage box should be sealed.
 - c. Prohibit exposure to moisture and direct light
- 2) Shelf life

12 month from date of manufacture
- 3) Curing condition
 - a. Mixing ratio :Resin : Hardener = 100 : 33.3 (wt%)
 - b. Imbalanced mixing will might occur curing problem.

4. Properties (Temperature:25°C, Humidity:45%)

Item	Unit	Resin	Hardener
Color	-	Clear	Slight brown
Viscosity	Cps / 25°C	800~1,400	10~100
Specific gravity	-	1.10~1.20	0.95~1.05
Solid content	%	95±3	97±3
Hardness	Shore D	70 이상	

JP-105

987-4, GO-YEON RI, UNG-CHON MYEON, ULJU-GUN, ULSAN, KOREA

JEF-QC-037

(주)제일화성

A4(210mm X 297mm)