

# Floor coating

[Http://www.jeilchemical.com](http://www.jeilchemical.com)

## JP-3000S

### 1. Product use

Transparent epoxy paint used for increase close adhesion with sand and reinforce the adhesion between top part of paint and asphalt or ascon.

### 2. Features

- 1) Superior adhesive property.
- 2) Excellent heat-resistance, cold-resistance, flexibility.

### 3. Others

- 1) Storage requirements
  - a. Store in room temperature (25°C ± 5°C)
  - b. Storage box should be sealed.
  - c. Prohibit exposure to moisture and direct light

#### 2) Shelf life

12 month from date of manufacture

#### 3) Curing condition

- a. Mixing ratio : Resin : Hardener = 100 : 25 (wt%)
- b. Under the 5°C of work place temperature, the Curing time might be longer and occur bad chemical reaction.

### 4. Properties (Temperature:25°C, Humidity:45%)

Item	Unit	Resin	Hardener
Color	-	Clear	Brown
Viscosity	Cps / 25°C	10~20	5~10
Specific gravity	-	0.90~1.00	0.90~1.00
Drying time	Hr	4 Within	
Pot life	Hr	2 Within	
Curing time	Hr	24 More than	

JP-3000S

987-4, GO-YEON RI, UNG-CHON MYEON, ULJU-GUN, ULSAN, KOREA